

# coates

Indonesia

a subsidiary of  Mitsubishi Corporation



## TRIME<sup>®</sup> X-START

4x415W LED - 8,5M

**RUNNING TIME**  
80 litres tank  
145h

**Very  
Robust**



  
KUBOTA Z482E

**Full mine  
spec.  
trailer**



### APPLICATIONS



Constructions



Mining operations

# heavy duty mine spec.



*Illustrative picture for indicative purpose only*

Sales & Hire



0811 5958 484



[inquiries@ptcoates.com](mailto:inquiries@ptcoates.com)



[www.ptcoates.com](http://www.ptcoates.com)

# TECHNICAL DATA

Designed to provide an exceptional level of performance for every work on site ensuring the right balance between power and ease of use



Illustrative picture for indicative purpose only

## FEATURES

- Multi-directionally adjustable and tiltable floodlights
- 7 sections vertical tower 8,5 m, 340° rotatable
- Hyd mast operation
- Galvanized metalworks
- 80 µm industrial powder coating finishing
- Central lifting eye
- Sides forklift pockets for effective handling
- Plug & play, colour coded cables and connectors
- Guided main coiled cable to avoid damage during tower operation
- Control panel alarms for engine protection and fuel level indicator
- DSE 3110 + light sensor as std features
- Circuit breaker for electrical protection against overload
- External emergency stop button
- Certified wind stability up to 80 km/h
- 5 height adjustable stabilizers
- On board levels for guidance during stabilization
- Running time 145 hours on single tank
- Fitted on site tow trailer c/w foldable front draw bar
  - (road tow braked version as option)
- 1Kva outlet socket

## LED TECHNOLOGY

**12000sqm**  
Illuminated area



Self-sufficient engine powered unit

## TECHNICAL DATA

| Dimension & weight | Roughly dimension min (mm) |              | Roughly dimensions max (mm) |                      | Roughly weight (Kg)    |
|--------------------|----------------------------|--------------|-----------------------------|----------------------|------------------------|
|                    | 2560x1370x2560 (LxWxH)     |              | 2560x2570x8000 (LxWxH)      |                      | 890                    |
| Floodlights        | Type                       | Power (each) | Floodlights number          | IP level             | Illuminated Area (sqm) |
|                    | LED                        | 415W         | 4                           | 67                   | 12000                  |
| Mast               | Lifting Method             | Max Height   | Max Wind Speed              | Rotation             |                        |
|                    | Hydraulic                  | 8,5 m        | 80 km/h                     | 340°                 |                        |
| Alternator         | Model                      | Rated Output | Voltage                     | Degree of protection |                        |
|                    | Synchronous                | 3.5 kVA      | 230V                        | IP 23                |                        |
| Engine             | Model                      | rpm          | Tank capacity               | Fuel consumption     |                        |
|                    | Kubota Z482E, 2-cylinders  | 1500         | 80l                         | 0.55 l/h             |                        |